

TRACTOR TRUCK MZKT-740100

SPECIFICATIONS

PERFORMANCE DATA

Wheel drive	8x8
Max. speed, km/h	80
Angle of approach	27°
Angle of departure	27°
Ground clearance, mm	380
Turning radius (curb to curb), m	12,5
Fuel tank capacity, I	800

WEIGHT DATA

Curb vehicle weight, kg	16 650
Fifth wheel load, kg	27 000
Gross vehicle weight, kg	43 800
Permissible weight on axles, kg	

front axles 2x9 300 rear axles 2x12 600

ENGINE

Number and location of cylinders	V8
Power	294 kW (400 h.p.) at 1900 min ⁻¹
Max. torque	1715 Nm

TRANSMISSION

Туре	manual
Number of gears	9 forward, 1 reverse
Gearratio	10.08-0.788

TRANSFER CASE

Number of gears

DRIVING AXLES 1-ST AND 2-ND

Steered, central reduction gears with interaxle differential locks

3-RD AND 4-TH

Central reduction gears with interaxle differential locks

AXLE SUSPENSION

Front-leaf spring Reverse-leaf spring balaced

BRAKE SYSTEM

Pneumatic drive ABS

TYRES

16.00R20

High cross-country capability Central tyre inflation system (CTIS)

FRAME

Longitudinal

Equipped with front and rear towing units

CAB

Full metal, 2-seat, 2 sleeping berths, air suspended driver's seat. Equipped with heating and ventilation systems

FIFTH WHEEL

Two degree of freedom, ø 3 1/2"

ELECTRICAL EQUIPMENT

Nominal voltage 24V Batteries 2pcs. 190 Ah

OPTIONS

1

Two-speed transfer case
Engine heater
Autonomous cab heater
Air condition system
Heated fuel filter
Spark arrester
Tachograph
Air suspended passenger's seat

Cab cover



