

CRANE CHASSIS MZKT-750002

SPECIFICATIONS

14 700

PERFORMANCE DATA

Wheel drive	8x8
Max. speed, km/h	80
Turning radius, m	15,5
Fuel tank capacity, I	350

WEIGHT DATA

Curb vehicle data, kg	14 700
Gross vehicle weight, kg	46 000
Permissible weight on axles, kg	
on 1-2 axles	2x10 000
on 3-4 axles	2x13 000
Weight of mounted equipment, kg	31 150

ENGINE

Ecology		EURO-V
Number and location	n of cylinders	L6
Max. power	308,8 kW (420	h.p.) at 1900 min ¹
Max. torque	1 985 Nm a	t 1100-1300 min 1

CLUTCH

Single-disc

TRANSMISSION

Type	manual
Number of gears	9 forward, 1 reverse
Gear ratio	13.96-0.73; R13.96

DRIVING AXLES

Rigid, with central reduction gears, interaxle and cross-axle differential lock

1st and 2nd axles-steered

AXLE SUSPENSION

1st and 2nd axles - dependent leaf-spring 3rd and 4th axles - dependent spring-balanced

BRAKE SYSTEM

Drum brakes of shoe-type with pneumatic drive Dual-circuit system Engine brake **ABS**

TYRES

16.00R20, offroad Central tyre inflation system (CTIS) Single wheels Number of wheels - 8+1

FRAME

Longitudinal

CAB

3-seat full-metal Equipped with ventilation and heating systems Driver seat - air-suspended

ELECTRICAL EQUIPMENT

Nominal voltage 24V Single-wire Batteries 2x190 Ah

OPTIONS

Liquid engine heater Battery container with heating Autonomous cab heater Air-conditioner

