

TRUCK CHASSIS MZKT-750004-010-01

SPECIFICATIONS

16 300

PERFORMANCE DATA

Wheel drive	8x8
Max. speed, km/h	60
Turning radius, m	18,5
Fuel tank capacity, I	500

WEIGHT DATA Curb vehicle data, kg

Gross vehicle weight, kg	46 000
Permissible weight on axles, kg	
on 1-2 axles	2x10 000
on 3-4 axles	2x13 000
Weight of mounted equipment, kg	29 700

ENGINE

Ecology		EURO-V
Number and locati	on of cylinders	L6
Max. power	308,8 kW (420 h.)	p.) at 1900 min ⁻¹
Max. torque	1 985 Nm at 1	1100-1300 min ⁻¹

CLUTCH

Single-disc

TRANSMISSION

Type	manual
Model	MZKT
Number of gears	9 forward, 1 reverse
Gear ratio	10.08-0.79; R9.55

DRIVING AXLES

Rigid, with central reduction gears, interaxle and cross-axle differential lock

1st and 2nd axles-steered

AXLE SUSPENSION

1st and 2nd axles - dependent leaf-spring 3rd and 4th axles - dependent spring-balanced

BRAKE SYSTEM

Drum brakes of shoe-type with pneumatic drive Dual-circuit system Engine brake ABS

TYRES

16.00R20, offroad Central tyre inflation system (CTIS) Single wheels Number of wheels - 8+1

FRAME

Longitudinal

Equipped with two front and one rear towing units, rear protection unit

CAB

2-seat full-metal Equipped with ventilation and heating systems Driver and passenger seats - air-suspended


ELECTRICAL EQUIPMENT


Nominal voltage 24V Single-wire Batteries 2x190 Ah

OPTIONS

Liquid engine heater
Battery container with heating
Autonomous cab heater
Air-conditioner

* Specifications can be clarified in the process of improving the design





E-Mail: link@mzkt.by www.mzkt.by