



TRUCK CHASSIS

MZKT-800300

TRUCK CHASSIS MZKT-800300

SPECIFICATIONS

PERFORMANCE DATA

12x12 Wheel drive Pneumohydraulic drive Maximum speed, km/h 45 Double-circuit Minimum curb-to-curb turning radius, m 16 700 Fuel tanks capacity, I

Maximum gradeability on dry hard ground, deg up to 20

WEIGHT DATA

Curb chassis weight, kg 31 000 44 000 Chassis load-carrying capacity, kg 75 000 Gross chassis weight, kg Permissible axle loads, kg 1st, 2nd and 3d axles 3x12 500 4th, 5th and 6th axles 3x12 500

ENGINE

Number and location of

cylinders L6 403 kW (550 h.p.) at 2100 min⁻¹ Power

TRANSMISSION

Type automatic 6 forward, 2 reverse Number of gears

POWER TAKE-OFF

Main - from flange of transfer case Additional - from power take-off at automatic transmission

TRANSFER CASE

Number of gears

BRAKE SYSTEM

TYRES

Central tyre inflation system 16.00R20 (Бел-95)

PLATFORM-FRAME

Longitudinal

Equipped with front and rear towing units


Reinforced steel bumper

Platform plating - 4 mm plate with one-side riffling


Full-metal, increased comfort One-seat


OPTIONS

Liquid engine heater Fuel heater Heating fuel intake Powerful heater Air conditioner Headlight protection



1





Tel.: +375 (17) 330-19-54; Fax.: +375 (17) 291-31-92; E-Mail: link@mzkt.by

www.mzkt.by